

LUBRICANT SPRAY PREMIUM W-MP



SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

ISSUE DATE: 25.07.2014
REVISION DATE: 08.08.2022
SUPERSEDES: 04.11.2019
VERSION: 6.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Lubricant Spray Premium W-MP
Product code : Ford Int. Ref. No.: 169990
SDS Number : 4109
UFI : SES5-9G45-7001-77J8
Vaporizer : Aerosol
Product use : Public use

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category : Lubricant

1.2.2. Uses advised against

Restrictions on use : None known

1.3. Details of the supplier of the safety data sheet

Supplier

Ford-Werke GmbH
Edsel-Ford-Str. 2-14
50769 Cologne
Germany
+49 221 90-33333
sdseu@ford.com

Distributor

Ford Motor Company Ltd.
Parts Distribution Centre
Royal Oak Way South
NN11 8NT Daventry, Northants
United Kingdom
+44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH – 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Physical hazards	Aerosol, Category 1	H222;H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Health hazards	Skin corrosion/irritation, Category 2 Specific target organ toxicity – Single exposure, Category 3, Narcosis	H315 H336	Causes skin irritation. May cause drowsiness or dizziness.
Environmental hazards	Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411	Toxic to aquatic life with long lasting effects.

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Hazard pictograms



Signal word

Danger

Contains

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.

Response

P391	Collect spillage.
------	-------------------

Storage

P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal

P501	Dispose of contents and container to an approved waste disposal plant.
------	--

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	- 921-024-6 - 01-2119475514-35-XXXX	75 - 90	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	UVCB
Carbon dioxide	124-38-9 204-696-9	2,5 - 5	Press. Gas (Comp.), H280	

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25-XXXX	2,5 - 5	Asp. Tox. 1, H304	(Note L)
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8 265-158-7 649-468-00-3 01-2119487077-29-XXXX	2,5 - 5	Asp. Tox. 1, H304	(Note L)
Dodecylamine	124-22-1 204-690-6 - 01-2119484818-20-XXXX	0,025 - < 0,25	Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	

Comments : Substances of Unknown or Variable composition, Complex reaction products or Biological materials

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell. Never give anything by mouth to an unconscious person.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
- First-aid measures after ingestion : Rinse mouth. Do not induce vomiting because of corrosive effects. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects: : May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol.
- Explosion hazard : Pressurised container: May burst if heated.
- Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon oxides (CO, CO₂).

5.3. Advice for firefighters

- Precautionary measures fire : Cool containers exposed to heat with water spray and remove container, if no risk is involved.
- Firefighting instructions : Use standard firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep unnecessary personnel away. Avoid inhalation of vapours.

6.1.1. For non-emergency personnel

Protective equipment : Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment.

6.3. Methods and material for containment and cleaning up

For containment : Prevent product from entering drains. Dispose of waste in accordance with environmental legislation.

Methods for cleaning up : Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Stop leak if safe to do so. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Other information : Never return spills in original containers for re-use. Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 : " Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing spray, vapours, aerosol. Avoid contact with skin and eyes. Wear personal protective equipment. Ensure good ventilation of the work station.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Store at temperatures not exceeding 50 °C. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Incompatible materials : Store away from incompatible materials (see Section 10 of the SDS).

Storage area : Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3. Specific end use(s)

Lubricant.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Carbon dioxide (124-38-9)

United Kingdom - Occupational Exposure Limits

Local name	Carbon dioxide
------------	----------------

WEL TWA (OEL TWA) [1]	9150 mg/m ³
WEL TWA (OEL TWA) [2]	5000 ppm
WEL STEL (OEL STEL)	27400 mg/m ³
WEL STEL	15000 ppm
Regulatory reference	EH40/2005 (Third edition, 2018). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (-)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	773 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2035 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, oral	699 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	608 mg/m ³
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day

Dodecylamine (124-22-1)

DNEL/DMEL (Workers)

Acute - local effects, inhalation	1 mg/m ³
Long-term - systemic effects, inhalation	0.38 mg/m ³
Long-term - local effects, inhalation	1 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, oral	40 µg/kg bw/day
Long-term - systemic effects, inhalation	0.035 mg/m ³

PNEC (Water)

PNEC aqua (freshwater)	0.26 µg/L
PNEC aqua (marine water)	0.026 µg/L
PNEC aqua (intermittent, freshwater)	1.6 µg/L

PNEC (Sediment)

PNEC sediment (freshwater)	3.76 mg/kg dwt
PNEC sediment (marine water)	0.376 mg/kg dwt

PNEC (Soil)

PNEC soil	10 mg/kg dwt
-----------	--------------

PNEC (STP)

PNEC sewage treatment plant	550 µg/L
-----------------------------	----------

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.73 mg/m ³
Long-term - local effects, inhalation	5.58 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day

PNEC (Oral)

PNEC oral (secondary poisoning) 9.33 mg/kg food Food/feed stuff

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)**DNEL/DMEL (Workers)**

Long-term - systemic effects, dermal 0.97 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 2.73 mg/m³

Long-term - local effects, inhalation 5.58 mg/m³

DNEL/DMEL (General population)

Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day

PNEC (Oral)

PNEC oral (secondary poisoning) 9.33 mg/kg food

8.1.5. Control banding

No additional information available

8.2. Exposure controls**8.2.1. Appropriate engineering controls****Appropriate engineering controls:**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment**8.2.2.1. Eye and face protection****Eye protection:**

Safety glasses

8.2.2.2. Skin protection**Skin and body protection:**

Wear suitable protective clothing

Hand protection:

Protective gloves. EN 374. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove

Material	Permeation	Thickness (mm)	Comments
Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
In case of splash contact:	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

Other skin protection**Materials for protective clothing:**

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment

8.2.2.3. Respiratory protection**Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment. EN 141. Type AX - Low-boiling (<65 °C) organic compounds. Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: whitish.
Appearance	: Aerosol.
Odour	: Characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 100 °C
Flammability	: Extremely flammable aerosol
Explosive properties	: In use, may form flammable/explosive vapour-air mixture. Pressurised container: May burst if heated.
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: -1 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Poorly soluble in water.
Log Kow	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 0.75 g/cm ³
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 77

9.2.2. Other safety characteristics

VOC content : 77.08 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidising agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Based on available data, the classification criteria are not met
Acute toxicity (dermal) : Based on available data, the classification criteria are not met
Acute toxicity (inhalation) : Based on available data, the classification criteria are not met

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (-)

LD50 dermal rat	> 2800 (2800 – 3100) mg/kg bodyweight
-----------------	---------------------------------------

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Based on available data, the classification criteria are not met
Carcinogenicity	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Based on available data, the classification criteria are not met
STOT-single exposure	: May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (-)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Dodecylamine (124-22-1)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Based on available data, the classification criteria are not met

Dodecylamine (124-22-1)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard : Based on available data, the classification criteria are not met

Lubricant Spray Premium W-MP

Vaporizer	Aerosol
-----------	---------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Based on available data, the classification criteria are not met

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (-)

Persistence and degradability Readily biodegradable.

Biodegradation 98 % (OECD 301F method)

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Lubricant Spray Premium W-MP

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Do not allow this material to drain into sewers/water supplies.
Product/Packaging disposal recommendations : Empty containers should be taken to an approved waste handling site for recycling or disposal. Container under pressure. Do not drill or burn even after use. a hazardous or special waste collection point.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR) : UN 1950
UN-No. (IMDG) : UN 1950
UN-No. (IATA) : UN 1950
UN-No. (ADN) : UN 1950
UN-No. (RID) : UN 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable
Proper Shipping Name (ADN) : AEROSOLS
Proper Shipping Name (RID) : AEROSOLS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1
Danger labels (ADR) : 2.1

IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1

IATA

Transport hazard class(es) (IATA) : 2.1
Hazard labels (IATA) : 2.1

ADN

Transport hazard class(es) (ADN) : 2.1
Danger labels (ADN) : 2.1

RID

Transport hazard class(es) (RID) : 2.1
Danger labels (RID) : 2.1

14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : Yes
Marine pollutant : Yes
Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Refer to the safety data sheet before handling or disposing

Overland transport

Classification code (ADR) : 5F
Special provisions (ADR) : 190, 327, 344, 625
Limited quantities (ADR) : 1I
Packing instructions (ADR) : P207
Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG) : P207, LP200
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A145, A167, A802
ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F
Special provisions (ADN) : 190, 327, 344, 625
Limited quantities (ADN) : 1 L

Rail transport

Classification code (RID) : 5F
Special provisions (RID) : 190, 327, 344, 625
Limited quantities (RID) : 1L
Packing instructions (RID) : P207, LP200
Hazard identification number (RID) : 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3(a)	Lubricant Spray Premium W-MP ; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
3(b)	Lubricant Spray Premium W-MP ; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ; 2-ethylhexanoic acid ; Distillates (petroleum), hydrotreated heavy paraffinic ; Distillates (petroleum), hydrotreated light paraffinic
3(c)	Lubricant Spray Premium W-MP ; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
40.	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 77.08 %

Other information, restriction and prohibition regulations : Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. Directive 94/33/EC on the protection of young people at work, as amended. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. For details, refer to section 3 and 8.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : Not applicable

Seveso III Part I (Categories of dangerous substances)

	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3b FLAMMABLE AEROSOLS	5000	50000
'Flammable' aerosols Category 1 or 2, not containing flammable gases Category 1 or 2 nor flammable liquids category 1		

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Section 1 - Section 16.

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
DPD	Dangerous Preparations Directive 1999/45/EC
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration

NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
OEL	Occupational Exposure Limit
RRN	REACH Registration no.
TWA	Time Weighted Average. The average concentration of a chemical in air over the total exposure time-usually an 8-hour workday.
WES	Workplace Exposure Standard – The airborne concentration of a biological or chemical agent to which a worker may be exposed
VOC	Volatile organic compounds
STEL	Short-term Exposure Limit

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H- and EUH-statements

Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Aerosol 1	H222;H229	On the basis of test data
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 2	H411	Calculation method

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Attachment to the Safety Data Sheet

Product Name: Lubricant Spray Premium W-MP

Ford Int. Ref. No.: 169990

Revision Date: 08.08.2022

Involved Products:

Finiscode	Part number	Container Size:
1 1 321 554	3S5J 1C26 AA	200 ml