

ACTIVATOR H-TT



SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

ISSUE DATE: 20.01.2022
REVISION DATE: 20.01.2022

VERSION: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Activator H-TT
Product code : Ford Internal Ref.: 505688
SDS Number : 9290
UFI : 4KG5-7F9J-010A-H7M6
Product use : Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category : Coatings and paints, thinners, paint removers

1.2.2. Uses advised against

Restrictions on use : None known

1.3. Details of the supplier of the safety data sheet

Supplier

Ford-Werke GmbH
Edsel-Ford-Str. 2-14
50769 Cologne
Germany
+49 221 90-33333
sdseu@ford.com

Distributor

Ford Motor Company Ltd.
Parts Distribution Centre
Royal Oak Way South
NN11 8NT Daventry, Northants
United Kingdom
+44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH – 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Physical hazards	Flammable liquids, Category 2	H225	Highly flammable liquid and vapour.
Health hazards	Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
	Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
	Respiratory sensitisation, Category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
	Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Hazard pictograms



Signal word

Danger

Contains

butanone, ethyl acetate, PPG-MDI-Prepolymer, < 0.1 % MDI, 4,4'-methylenediphenyl diisocyanate

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336	May cause drowsiness or dizziness.

Precautionary statements

Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapours, gas, fume.
P280	Wear eye protection, protective gloves, protective clothing.

Response

P342+P311	If experiencing respiratory symptoms: Call doctor, a POISON CENTER.
P370+P378	In case of fire: Use carbon dioxide (CO ₂), D-powder, foam to extinguish.

Storage

P403+P235	Store in a well-ventilated place. Keep cool.
-----------	--

Extra phrases As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

Other hazards which do not result in classification : Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43-XXXX	40 – 60	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	#
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46-XXXX	20 – 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	#
PPG-MDI-Prepolymer, < 0.1 % MDI	9048-57-1 500-028-8	10 -< 20	Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334	

			Skin Sens. 1, H317 STOT SE 3, H335	
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29-XXXX	5 -< 10	Flam. Liq. 3, H226 STOT SE 3, H336	
Tris(p-isocyanatophenyl) thiophosphate	4151-51-3 223-981-9 01-2119948848-16-XXXX	5 -< 10	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight)	
4,4'-methylenediphenyl diisocyanate	101-68-8 202-966-0 615-005-00-9 01-2119457014-47-XXXX	0,01 -< 0,1	Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	(0.1 ≤C ≤ 100) Resp. Sens. 1, H334 (5 ≤C ≤ 100) Eye Irrit. 2, H319 (5 ≤C ≤ 100) Skin Irrit. 2, H315 (5 ≤C ≤ 100) STOT SE 3, H335 (Note C)(Note 2)

Comments : #: substance with a Community workplace exposure limit

Note 2 : The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Never give anything by mouth to an unconscious person.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
- First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist if irritation persists.
- First-aid measures after ingestion : Do not induce vomiting. Rinse mouth out with water. Drink plenty of water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects: : May cause drowsiness or dizziness.
- Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
- Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed. Carbon oxides (CO, CO₂).

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop the flow of material, if this is without risk. Move containers from fire area if it can be done without personal risk.

Methods for cleaning up : Large Spills: Stop leak if safe to do so. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing fume, vapours. Avoid contact with skin and eyes.

Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Use non-sparking tools.

Incompatible products : Keep away from open flames, hot surfaces and sources of ignition.

Storage temperature : 5 – 40 °C

7.3. Specific end use(s)

Adhesives, sealants.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

butanone (78-93-3)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Butanone
IOEL TWA	600 mg/m ³
IOEL TWA [ppm]	200 ppm
IOEL STEL	900 mg/m ³
IOEL STEL [ppm]	300 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

United Kingdom - Occupational Exposure Limits

Local name	Butan-2-one (methyl ethyl ketone)
WEL TWA (OEL TWA) [1]	600 mg/m ³
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	899 mg/m ³
WEL STEL	300 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

United Kingdom - Biological limit values

Local name	Butan-2-one (methyl ethyl ketone)
BMGV	70 µmol/l Parameter: butan-2-one - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

ethyl acetate (141-78-6)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Ethyl acetate
IOEL TWA	734 mg/m ³
IOEL TWA [ppm]	200 ppm
IOEL STEL	1468 mg/m ³
IOEL STEL [ppm]	400 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164

United Kingdom - Occupational Exposure Limits

Local name	Ethyl acetate
WEL TWA (OEL TWA) [1]	734 mg/m ³
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	1468 mg/m ³
WEL STEL	400 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

n-butyl acetate (123-86-4)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	n-Butyl acetate
------------	-----------------

IOEL TWA	241 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m ³
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831

United Kingdom - Occupational Exposure Limits

Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m ³
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m ³
WEL STEL	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

butanone (78-93-3)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	1161 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	600 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, oral	31 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	106 mg/m ³
Long-term - systemic effects, dermal	412 mg/kg bodyweight/day

PNEC (Water)

PNEC aqua (freshwater)	55.8 mg/l
PNEC aqua (marine water)	55.8 mg/l
PNEC aqua (intermittent, freshwater)	55.8 mg/l

PNEC (Sediment)

PNEC sediment (freshwater)	284.74 mg/kg dwt
PNEC sediment (marine water)	284.7 mg/kg dwt

PNEC (Soil)

PNEC soil	22.5 mg/kg dwt
-----------	----------------

PNEC (Oral)

PNEC oral (secondary poisoning)	1000 mg/kg food
---------------------------------	-----------------

PNEC (STP)

PNEC sewage treatment plant	709 mg/l
-----------------------------	----------

ethyl acetate (141-78-6)

DNEL/DMEL (Workers)

Acute - systemic effects, inhalation	1468 mg/m ³
Acute - local effects, inhalation	1468 mg/m ³

Long-term - systemic effects, dermal	63 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	734 mg/m ³
Long-term - local effects, inhalation	734 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	734 mg/m ³
Acute - local effects, inhalation	734 mg/m ³
Long-term - systemic effects, oral	4.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	367 mg/m ³
Long-term - systemic effects, dermal	37 mg/kg bodyweight/day
Long-term - local effects, inhalation	367 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.24 mg/l
PNEC aqua (marine water)	0.024 mg/l
PNEC aqua (intermittent, freshwater)	1.65 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1.15 mg/kg dwt
PNEC sediment (marine water)	0.115 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.148 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0.2 g/kg food
PNEC (STP)	
PNEC sewage treatment plant	650 mg/l

n-butyl acetate (123-86-4)

DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	11 mg/kg bodyweight/day
Acute - systemic effects, inhalation	600 mg/m ³
Acute - local effects, inhalation	600 mg/m ³
Long-term - systemic effects, dermal	11 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	300 mg/m ³
Long-term - local effects, inhalation	300 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	6 mg/kg bodyweight
Acute - systemic effects, inhalation	300 mg/m ³
Acute - systemic effects, oral	2 mg/kg bodyweight
Acute - local effects, inhalation	300 mg/m ³
Long-term - systemic effects, oral	2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	35.7 mg/m ³
Long-term - systemic effects, dermal	6 mg/kg bodyweight/day
Long-term - local effects, inhalation	35.7 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.18 mg/l

PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.098 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.09 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	35.6 mg/l

Tris(p-isocyanatophenyl) thiophosphate (4151-51-3)

DNEL/DMEL (Workers)

Long-term - local effects, inhalation 0.047 mg/m³

PNEC (Water)

PNEC aqua (freshwater) 0.1 mg/l

PNEC aqua (marine water) 0.01 mg/l

PNEC aqua (intermittent, freshwater) 1 mg/l

PNEC (Sediment)

PNEC sediment (freshwater) 2557 mg/kg dwt

PNEC sediment (marine water) 155 mg/kg dwt

PNEC (Soil)

PNEC soil 510 mg/kg dwt

PNEC (STP)

PNEC sewage treatment plant 100 mg/l

4,4'-methylenediphenyl diisocyanate (101-68-8)

DNEL/DMEL (Workers)

Acute - local effects, inhalation 0.1 mg/m³

Long-term - local effects, inhalation 0.05 mg/m³

DNEL/DMEL (General population)

Acute - local effects, inhalation 0.05 mg/m³

Long-term - local effects, inhalation 0.025 mg/m³

PNEC (Water)

PNEC aqua (freshwater) 1 mg/l

PNEC aqua (marine water) 0.1 mg/l

PNEC aqua (intermittent, freshwater) 10 mg/l

PNEC (Soil)

PNEC soil 1 mg/kg dwt

PNEC (STP)

PNEC sewage treatment plant 1 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. EN 166. Safety glasses with side shields

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves. EN 374. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove

Material	Permeation	Thickness (mm)	Comments
Butyl rubber	60 - 119 min	0,7	Glove recommendation: Butoject® 898 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
In case of splash contact: Butyl rubber	60 - 119 min	0,7	Glove recommendation: Butoject® 898 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection. Type A - High-boiling (>65 °C) organic compounds

8.2.2.4. Thermal hazards

Thermal hazard protection:

Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: solvents-like.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 79 °C
Flash point	: -4 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 430 mbar @ 55°C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.9 g/cm ³
Solubility	: No data available
Log Pow	: No data available

Viscosity, kinematic	: No data available
Viscosity, dynamic	: 2 – 12 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC (EU)	: 75.5 %
----------	----------

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. During fire, gases hazardous to health may be formed. Carbon oxides (CO, CO₂). On exposure to high temperature, may decompose, releasing : Isocyanates.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Based on available data, the classification criteria are not met
Acute toxicity (dermal)	: Based on available data, the classification criteria are not met
Acute toxicity (inhalation)	: Based on available data, the classification criteria are not met

Activator H-TT	
ATE CLP (oral)	> 2000 mg/kg
ATE CLP (gases)	> 20000 ppm/4h
ATE CLP (vapours)	> 20 mg/l
ATE CLP (dust,mist)	> 5 mg/l

PPG-MDI-Prepolymer, < 0.1 % MDI (9048-57-1)	
LC50 Inhalation - Rat (Dust/Mist)	1.38 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Additional information	: Persons suffering from allergic reactions to isocyanates should avoid contact with the product.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met
Carcinogenicity	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Based on available data, the classification criteria are not met
STOT-single exposure	: May cause drowsiness or dizziness.

butanone (78-93-3)	
STOT-single exposure	May cause drowsiness or dizziness.

ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
PPG-MDI-Prepolymer, < 0.1 % MDI (9048-57-1)	
STOT-single exposure	May cause respiratory irritation.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
4,4'-methylenediphenyl diisocyanate (101-68-8)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Based on available data, the classification criteria are not met
4,4'-methylenediphenyl diisocyanate (101-68-8)	
STOT-repeated exposure	May cause damage to organs (respiratory system) through prolonged or repeated exposure (inhalation).
Aspiration hazard	: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Hazardous to the aquatic environment, short-term (acute)	: Based on available data, the classification criteria are not met
Hazardous to the aquatic environment, long-term (chronic)	: Based on available data, the classification criteria are not met

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

n-butyl acetate (123-86-4)

Log Pow	1.78
---------	------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Activator H-TT

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Other adverse effects

Other adverse effects	: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.
-----------------------	---

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations.
Waste treatment methods	: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not allow this material to drain into sewers/water supplies.

Product/Packaging disposal recommendations	: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Additional information	: Flammable vapours may accumulate in the container. Disposal must be done according to official regulations.
European List of Waste (LoW) code	: The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number

UN-No. (ADR)	: UN 1139
UN-No. (IMDG)	: UN 1139
UN-No. (IATA)	: UN 1139
UN-No. (ADN)	: UN 1139
UN-No. (RID)	: UN 1139

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: COATING SOLUTION
Proper Shipping Name (IMDG)	: COATING SOLUTION
Proper Shipping Name (IATA)	: Coating solution
Proper Shipping Name (ADN)	: COATING SOLUTION
Proper Shipping Name (RID)	: COATING SOLUTION

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3

IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3

IATA

Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3

ADN

Transport hazard class(es) (ADN)	: 3
Danger labels (ADN)	: 3

RID

Transport hazard class(es) (RID)	: 3
Danger labels (RID)	: 3

14.4. Packing group

Packing group (ADR)	: II
Packing group (IMDG)	: II
Packing group (IATA)	: II
Packing group (ADN)	: II
Packing group (RID)	: II

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available.

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 640D
Limited quantities (ADR)	: 5L
Packing instructions (ADR)	: P001, IBC02, R001
Hazard identification number (Kemler No.)	: 33
Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

Transport by sea

Limited quantities (IMDG)	: 5 L
Packing instructions (IMDG)	: P001
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 640D
Limited quantities (ADN)	: 5 L

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 640D
Limited quantities (RID)	: 5L
Packing instructions (RID)	: P001, IBC02, R001
Hazard identification number (RID)	: 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3(a)	Activator H-TT ; butanone ; ethyl acetate ; n-butyl acetate
3(b)	Activator H-TT ; butanone ; ethyl acetate ; PPG-MDI-Prepolymer, < 0.1 % MDI ; n-butyl acetate
40.	butanone ; ethyl acetate ; n-butyl acetate
56.	4,4'-methylenediphenyl diisocyanate
56(a)	4,4'-methylenediphenyl diisocyanate
74.	4,4'-methylenediphenyl diisocyanate

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 75.5 %

Other information, restriction and prohibition regulations : Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. Directive 94/33/EC on the protection of young people at work, as amended. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. For details, refer to section 3 and 8.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : Not applicable

Seveso III Part I (Categories of dangerous substances)

	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS	5000	50000
Flammable liquids, Categories 2 or 3 not covered by P5a and P5b		

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

None.

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified

vPvB Very Persistent and Very Bioaccumulative
ED Endocrine disrupting properties

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Training advice : Follow training instructions when handling this material.

Full text of H- and EUH-statements

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Flam. Liq. 2	H225	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Attachment to the Safety Data Sheet

Product Name: Activator H-TT

Ford Int. Ref. No.: 505688

REVISION DATE: 20.01.2022

Involved Products:

Finiscode	Part number	Container Size:
1 2 605 768	MU7J 2771 AA	10 ml