



SEALANT DB-PF

SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

ISSUE DATE: 06.09.2022
REVISION DATE: 06.09.2022

VERSION: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Sealant DB-PF
Product code : Ford Internal Ref: 507883
SDS Number : 10259
UFI : P1KC-6FAW-910K-GJPT
Product use : For professional users only

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category : Adhesives, sealants

1.2.2. Uses advised against

Restrictions on use : None known

1.3. Details of the supplier of the safety data sheet

Supplier

Ford-Werke GmbH
Edsel-Ford-Str. 2-14
50769 Cologne
Germany
+49 221 90-33333
sdseu@ford.com

Distributor

Ford Motor Company Ltd.
Parts Distribution Centre
Royal Oak Way South
NN11 8NT Daventry, Northants
United Kingdom
+44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH – 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Physical hazards	Flammable liquids, Category 3	H226	Flammable liquid and vapour.
Health hazards	Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Hazard pictograms



Signal word

Warning

Contains 2-methoxy-1-methylethyl acetate

Hazard statements

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing fume, gas, spray, vapours.

Response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P312 Call a POISON CENTER, doctor if you feel unwell.

Storage

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Other hazards which do not result in classification : In use may form flammable/explosive vapour-air mixture. In high concentrations vapours cause anaesthetic and narcotic effect. May be irritating to the mucous membranes and to the respiratory system.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29-XXXX	30 -< 50	Flam. Liq. 3, H226 STOT SE 3, H336	#

Comments : #: substance with a Community workplace exposure limit

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Never give anything by mouth to an unconscious person.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist if irritation persists.

First-aid measures after ingestion : Do not induce vomiting. Rinse mouth out with water. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects: : May cause drowsiness or dizziness. nausea, vomiting. Headache. irritation of mucous membranes.
Symptoms/effects after inhalation : Headache. May cause drowsiness or dizziness. May cause respiratory irritation. Nausea. Vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour. Heat may cause pressure rise with explosion of tanks/drums.
Explosion hazard : Vapours may form explosive mixture with air.
Hazardous decomposition products in case of fire : Toxic fumes may be released. During fire, gases hazardous to health may be formed. Carbon oxides (CO, CO₂).

5.3. Advice for firefighters

- Precautionary measures fire : Containers should be cooled with water to prevent vapor pressure build up. Do not breathe fumes. Do not dispose of fire-fighting water in the environment. Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Stop leak if safe to do so. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In case of fire: evacuate area.
Firefighting instructions : Keep unnecessary personnel away.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, mist, spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
Methods for cleaning up : Large Spills: Stop leak if safe to do so. Dike the spilled material, where this is possible. Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing fume, gas, mist, spray, vapours.
Hygiene measures	: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent the build-up of electrostatic charge. Store in original container. Store locked up. Store tightly closed in a dry, cool and well-ventilated place. Always keep container in upright position. Protect from sunlight. Do not pierce or burn, even after use.
Incompatible products	: Keep away from open flames, hot surfaces and sources of ignition. Oxidising agents. Strong bases.
Incompatible materials	: Natural rubber.
Information on mixed storage	: Refer to Section 10 on Incompatible Materials.

7.3. Specific end use(s)

Adhesives, Sealants.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

2-methoxy-1-methylethyl acetate (108-65-6)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	550 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

United Kingdom - Occupational Exposure Limits

Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA) [1]	274 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	548 mg/m ³
WEL STEL	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

2-methoxy-1-methylethyl acetate (108-65-6)

DNEL/DMEL (Workers)

Acute - local effects, inhalation	550 mg/m ³
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	275 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, oral	36 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	33 mg/m ³
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day
Long-term - local effects, inhalation	33 mg/m ³

PNEC (Water)

PNEC aqua (freshwater)	0.635 mg/l
PNEC aqua (marine water)	0.064 mg/l
PNEC aqua (intermittent, freshwater)	6.35 mg/l

PNEC (Sediment)

PNEC sediment (freshwater)	3.29 mg/kg dwt
PNEC sediment (marine water)	0.329 mg/kg dwt

PNEC (Soil)

PNEC soil	0.29 mg/kg dwt
-----------	----------------

PNEC (STP)

PNEC sewage treatment plant	100 mg/l
-----------------------------	----------

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment

Personal protective equipment:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. EN 166. Safety glasses with side shields

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves. EN 374. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove

Material	Permeation	Thickness (mm)	Comments
In case of splash contact:	6 (> 480 minutes)	0,7	Glove recommendation: Butoject® 898 (Kächele-Cama GmbH, source of

Butyl rubber

supply see www.kcl.de) or comparable product.

Butyl rubber 6 (> 480 minutes) 0,7

Glove recommendation: Butoject® 898 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

Other skin protection

Materials for protective clothing:

Wear suitable protective clothing.

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

Thermal hazard protection:

Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Grey.
Appearance	: Viscous.
Odour	: Ester.
Odour threshold	: Not available
Melting point	: -60 °C @ 101,3 kPa
Freezing point	: Not available
Boiling point	: 145 °C @ 101,3 kPa
Flammability	: Flammable liquid and vapour
Explosive properties	: Could form explosive mixtures with air.
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: 30 °C @ 101,3 kPa
Auto-ignition temperature	: 320 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: ≥ 5000 mm ² /s DIN EN ISO 2431
Solubility	: Not available
Log Kow	: Not available
Vapour pressure	: ≈ 3.5 hPa @ 101,3 kPa
Vapour pressure at 50 °C	: Not available
Density	: 1.2 g/l @ 20°C
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Avoid contact with : Strong bases. Strong oxidizers. Heat and ignition sources.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Based on available data, the classification criteria are not met
Acute toxicity (dermal) : Based on available data, the classification criteria are not met
Acute toxicity (inhalation) : Based on available data, the classification criteria are not met

Sealant DB-PF	
ATE CLP (oral)	> 2000 mg/kg
ATE CLP (dermal)	> 2000 mg/kg
ATE CLP (vapours)	> 20 mg/l

Skin corrosion/irritation : Based on available data, the classification criteria are not met
Serious eye damage/irritation : Based on available data, the classification criteria are not met
Respiratory or skin sensitisation : Based on available data, the classification criteria are not met
Germ cell mutagenicity : Based on available data, the classification criteria are not met
Carcinogenicity : Based on available data, the classification criteria are not met
Reproductive toxicity : Based on available data, the classification criteria are not met
STOT-single exposure : May cause drowsiness or dizziness.

2-methoxy-1-methylethyl acetate (108-65-6)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Based on available data, the classification criteria are not met
Aspiration hazard : Based on available data, the classification criteria are not met

Sealant DB-PF	
Viscosity, kinematic	≥ 5000 mm ² /s DIN EN ISO 2431

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Hazardous to the aquatic environment, short-term (acute) : Based on available data, the classification criteria are not met

Hazardous to the aquatic environment, long-term (chronic) : Based on available data, the classification criteria are not met

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Sealant DB-PF

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations.

Waste treatment methods : Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Container under pressure. Do not drill or burn even after use.

Additional information : Flammable vapours may accumulate in the container. Dispose in accordance with all applicable regulations.

European List of Waste (LoW) code : The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

15 01 10* - packaging containing residues of or contaminated by dangerous substances
08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR) : UN 1133

UN-No. (IMDG) : UN 1133

UN-No. (IATA) : UN 1133

UN-No. (ADN) : UN 1133

UN-No. (RID) : UN 1133

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ADHESIVES

Proper Shipping Name (IMDG) : ADHESIVES

Proper Shipping Name (IATA)	: Adhesives
Proper Shipping Name (ADN)	: ADHESIVES
Proper Shipping Name (RID)	: ADHESIVES

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3

IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3

IATA

Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3

ADN

Transport hazard class(es) (ADN)	: 3
Danger labels (ADN)	: 3

RID

Transport hazard class(es) (RID)	: 3
Danger labels (RID)	: 3

14.4. Packing group

Packing group (ADR)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III
Packing group (ADN)	: III
Packing group (RID)	: III

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available.

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Hazard identification number (Kemler No.)	: 30
Tunnel restriction code (ADR)	: D/E
EAC code	: •3Y

Transport by sea

Special provisions (IMDG)	: 223, 955
Limited quantities (IMDG)	: 5 L
Packing instructions (IMDG)	: P001, LP01
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L

CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1
Limited quantities (ADN) : 5 L

Rail transport

Classification code (RID) : F1
Limited quantities (RID) : 5L
Packing instructions (RID) : P001, IBC03, LP01, R001
Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3(a)	Sealant DB-PF ; 2-methoxy-1-methylethyl acetate
3(b)	Sealant DB-PF ; 2-methoxy-1-methylethyl acetate
40.	2-methoxy-1-methylethyl acetate

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 0 %

Other information, restriction and prohibition regulations : Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. Directive 94/33/EC on the protection of young people at work, as amended. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. For details, refer to section 3 and 8.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : Not applicable

Seveso III Part I (Categories of dangerous substances)

	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS	5000	50000
Flammable liquids, Categories 2 or 3 not covered by P5a and P5b		

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

None.

Abbreviations and acronyms

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Full text of H- and EUH-statements

Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Flam. Liq. 3	H226	On the basis of test data
STOT SE 3	H336	Calculation method

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Attachment to the Safety Data Sheet

Product Name: Sealant DB-PF

Ford Int. Ref. No.: 507883

Revision Date: 06.09.2022

Involved Products:

Finiscode	Part number	Container Size:
1 2 658 281	NU7J 473K20 AA	100 g